Date: _	
G.C	

			Paint So	Instructor Tips					
SMOHIT Safety Sense	Aetal Industry	•	Paint solvents are used to dissolve surfaces.	e paint, thi	n it out, or remove it from	<ul> <li>Remind workers to read</li> </ul>			
		•	Avoid inhaling solvent vapors as m there is adequate ventilation. Take leave the work site whenever you a paint solvents.	the MSDS or the label on the solvent container to					
		•	Always wear the appropriate persons safety goggles and chemical-resist or butyl. Never touch solvents dire	tant rubbe	r gloves made of neoprene	familiarize themselves with all adverse			
		•	Don't work in an area where there	effects of solvents.					
	neet /	•	Never transfer solvents into an unl drink container.	abeled co	ntainer, especially a food or				
	he Sh	•	Always wash your hands after usir eating, or drinking.						
Ŀ	for t	•	Keep solvent containers tightly cov not in use.						
9	lks	•	Never use a solvent as a hand clea						
SMC	Toolbox Tal	•	Inhalation of methylene chloride in converted by the body to carbon m ability to carry oxygen. However, if levels of carbon monoxide should						
		•	Health risks from exposure to pain duration of exposure. Symptoms of include eye irritation, dizziness, lig you experience any of these symp and do not resume the project unti through the work area. Individuals as shortness of breath or chest pa immediately.						
			-		lui i t				
1.			Name	Init.	<b>Name</b> 13.		Init.		
2.					14.				
3.					15.				
4.					16.				
5. 6.					17.				
6. 7.					18. 19.				
7. 8.					20.				
9.					21.				
10.					22.				
11.					23.				
12.					24.				